Z334-PUDF

RE-USE OEM
STEEL WASHERS

THICKER ONES TO BE
INSTALLED ON TOP

PROPELLER SHAFT BOLT TORQUE:
73,5Nm (54 lbf-ft)

POLY PARTS TO BE
INSTALLED FIRST

LUBRICATE HOLES WITH LITHIUM GREASE

DRIVESHAFT BOLT TORQUE:
72Nm (52 lbf-ft)

THINNER BUSHES TO BE
INSTALLED IN THE BOTTOM

LARGER HOLE TO FACE OUTSIDE

OEM BOLT TORQUE: 110Nm (81 lbf-ft)

OEM BOLT TORQUE: 100Nm (74 lbf-ft)

SUBFRAME HOLE TO BE LUBRICATED AND
BUSH TAPPED IN WITH RUBBER MALLET

RE-USE OEM STEEL WASHERS,
DISREGARD RUBBER ISOLATORS

PC NO	COMPONENT NAME	QTY
4	350Z POLY DIFF MOUNT - FRONT SLEEVE	2
3	350Z POLY DIFF MOUNT - FRONT BOTTOM	2
2	350Z POLY DIFF MOUNT - FRONT TOP	2
1	350Z POLY DIFF MOUNT - REAR	1